



Colour Touch Thermostat - W3WT01



Monitoring of energy consumption

Total switch-on can be read-out for overall energy consumption monitoring.

Factory-set of events

The thermostat is delivered with factory-set programs:

DAY 1-5 (working days)

EVENT TIME	TEMPERATURE
1 06:00-08:00	Comfort 20 °C
2 08:00-16:00	Setback 15 °C
3 16:00-23:00	Comfort 20 °C
4 16:00-23:00	Setback 15 °C

DAY 6-7 (home days)

EVENT TIME	TEMPERATURE
1 06:00-23:00	Comfort 20 °C
4 23:00-06:00	Setback 15 °C

Individual programming of events

The factory-set periods and/or temperatures can be adjusted as necessary.

The following programs can also be selected

Choose between 4- or 6-event scheduler. Up to seven different event program combinations can be used. Choose between method "work-/home-days" or "individual days" programming.

Comfort mode

The room temperature can be temporarily changed for a selected number of hours. The controlled thermostat will then return to the scheduled event program.

Manual mode

The scheduled event program can be cancelled for permanent constant temperature operation.

Holiday mode

Program a planned holiday period and the thermostat will start automatically.

Boost mode

Activate a boost period of one hour to rapidly increase the temperature. The thermostat will then return to normal operation.

Frost mode

Frost protection mode can be activated if no heat is needed. (Ensures no frost damages at low temperatures).

TECHNICAL DATA

Supply voltage	230 V AC $\pm 10\%$ 50/60 Hz
Standby power	< 0.36 Watt
Output relay SPST	16 A, resistive load or 1 A inductive load
Interrupter	2-pole, 16 A
Temperature range	+5/+40 °C
Floor limit range	+5/+40 °C
Clock function	Up to seven different 4- or 6-event program combinations
Battery backup	5 years storage
Ambient temperature	0/+40 °C during operation
On/Off differential	0.4 °C
Regulation principle	PWM / PI
Housing	IP21
Standard sensor type	NTC (12 K Ω) 3 m. Thermostat compatible with all common sensors on the market
Dimensions (H/W/D)	115/84/40 mm (21.8 mm depth)
Display	220 x 176 pixel TFT - Color resistive touch
EU Registered Design	Yes
Approvals:	CE

Warmup has heating experts and contractors nationwide, who will be pleased to provide more details on Warmup's products and services. To contact your local Warmup distributor or to arrange a free, no-obligation quotation, please call New Zealand: 0800 WARMUP (927 687) / Australia 1300 WARMUP (927 687).

warmup.co.nz | warmup.com.au